



NEW YORK YACHT CLUB
ROBERT H. TIEDEMANN CLASSIC REGATTA
June 26-27, 2021
Newport, Rhode Island

NOTICE OF RACE ADDENDUM 1 –NYYC CLASSICS RULES

These rules are in effect for all boats competing in classes using the CRF Rating. These rules do not apply to boats racing in a one-design class. For boats competing in the Classic Yachts Challenge Series, the Notice of Series (NOS) shall apply. For those boats, if there is a conflict between the 2021 Robert H. Tiedemann Classic Regatta Notice of Race, including this Addendum 1, the NOS shall apply.

1 GENERAL

- 1.1** The *Racing Rules of Sailing* (RRS) shall apply except as changed in the Notice of Race or Sailing Instructions.
- 1.2** All yachts competing in a race scored using CRF ratings must present a valid CRF 2021 Certificate.
- 1.3** Yachts may have only one valid CRF 2021 Certificate at a time, and are allowed to make just one configuration change during a calendar year. Corrections or minor updates to declared data need not be considered a configuration change.

2 DIVISIONS

- 2.1** Yachts may be assigned to divisions based on their original design date when they have been equipped and built with methods and materials consistent with that original design, or that are appropriate for their division.
- 2.2** Yachts may be grouped into divisions based on the following guidelines:
 - Vintage:** Yachts designed before January 1, 1950 and built, maintained, and restored with materials and methods reasonably consistent with the original design.
 - Classic:** Yachts designed on or after January 1, 1950 whose rudders are attached to the trailing edge of the keel with at least one pivot point on the sternpost, and that are rated by CRF with Keel Type 5 or Type 6.
 - Modern Classic:** Yachts designed on or after January 1, 1950 and typically before January 1, 1975, whose rudders are separated from the trailing edge of the keel and that are rated by CRF as Keel Type 3 or Type 4.
 - Spirit of Tradition:** Yachts typically designed on or after January 1, 1975 whose rudders are separated from the trailing edge of the keel and that are rated by CRF as Keel Type 1,2,3,or 4, and whose design embodies an appreciation of classic yacht or traditional workboat shapes and aesthetics. There are no

restrictions on rigging, equipment, or construction materials and methods for Spirit of Tradition (SoT) yachts.

- 2.3 The resolution of uncertainties or disputes regarding division assignments shall be at the sole discretion of the OA.

3 CLASSES and SCORING

- 3.1 When reasonable and practical, the minimum number of yachts in a class should be four. If the number of registered yachts in any division or class is less than four, the OA may consider combining that division or class with another division or class as appropriate.
- 3.2 All yachts shall declare whether they will race with either their 'spinnaker' or their 'non-spinnaker' rating, and no yacht shall be permitted to change that declaration during that event.

4 RIGGING and EQUIPMENT

- 4.1 A stay is defined as a permanently-secured and taut cable that supports a headsail. A removable stay shall be considered permanent if it is secured and kept in a taut condition for the duration of an event. This definition includes luff-ropes that allow a sail to be rolled on the rope.
- 4.2 Forestays and headsail tacks, except those of spinnaker staysails when the boat is not close-hauled, shall be attached approximately on a boat's centerline, in accordance with RRS 54.
- 4.3 The length of a spinnaker pole when used to pole out a spinnaker must be no longer than the SPL declared on the CRF Certificate. When in use, a spinnaker pole or whisker pole must be attached to the foremost mast in accordance with RRS 55.2.
- 4.4 Shifting ballast of any kind during a race, other than shifting crew weight, is not permitted. All ballast must be fixed in place against shifting. Other temporary means of augmenting stability are prohibited, including the use of trapezes. All crew must keep their torsos within the perimeter of the yacht except as allowed by RRS 49.
- 4.5 The use of stored-energy equipment, including powered winches and hydraulics, is permitted in all Divisions aboard yachts whose declared displacement is greater than 50,000 lbs. This changes RRS 52, 'Manual Power'.

5 SAILS

- 5.1 Yachts in the Vintage and Classic Divisions shall race with sails fabricated from materials limited to Polyester (e.g. Dacron), Nylon, or Ultra-PE (e.g. Spectra, Dyneema, UHMWPE, etc.). Inclusion of carbon fiber in the materials used is specifically not allowed.
- 5.2 Yachts in the Vintage and Classic Divisions shall race with upwind sails (e.g. those that are-attached to masts or stays) of classic light color. Resolution of uncertainties or disputes regarding upwind sail color shall be at the discretion of the OA.
- 5.3 Yachts in a Spirit of Tradition and Modern Classic Divisions may race with upwind sails built with any fiber via any sailmaking technique.

6 SETTING AND SHEETING SAILS (Spinnaker and non-spinnaker)

- 6.1 In accordance with RRS 55.4, a headsail is defined as a sail set forward of the mast spar, or of the foremost mast spar if more than one mast, where the measurement between the *half luff point* and the *half leech point* is less than 75% of the length of its foot. A spinnaker is a sail set forward of the mast spar, or of the foremost mast spar if more than one mast, where the measurement between the *half luff point* and the *half leech point* is equal to or greater than 75% of the foot length. A sail tacked down behind the foremost mast is not a headsail.
- 6.2 All headsails and staysails, except spinnaker staysails, shall be fully attached to stays, except while being set or struck. A sail is defined as "fully attached" to a stay when it is secured to the stay by at least four evenly-spaced hanks or other attachments, or is continuously secured to the stay by a luff-rope in a groove or other continuous attachment.
- 6.3 Only one headsail may be flown on each stay in the fore-triangle at a time. This requires that when sail changes are made, the sail to be replaced must be dropped to the deck before its replacement is set on the

same stay. This changes RRS 55.1.

- 6.4 In accordance with RRS 55.3 (a), a headsail may be sheeted or attached at its clew to a spinnaker pole or whisker pole, provided that a spinnaker is not set. When such a pole is used to wing out a jib, its length may not exceed 110% of 'J' unless reflected on the CRF certificate.
- 6.5 A yawl or ketch racing under a non-spinnaker rating shall not fly a mizzen spinnaker, but may fly a mizzen staysail. Any yacht that flies a mizzen spinnaker must race under a spinnaker rating. A mizzen staysail is an off wind sail hoisted from the mizzen mast whose mid-girth is less than 75% of its foot length. A mizzen spinnaker is an off wind sail hoisted from the mizzen mast whose mid-girth is equal to or greater than 75% of its foot length.
- 6.6 On schooners, a fisherman or gollywobbler is permitted.
- 6.7 A yacht shall not fly any sail whose dimensions exceed those shown on her CRF 2021 Certificate, and no headsail may be flown outside the limits defined by the IG (P2), J, and LP% shown on that certificate.

7 WIND LIMITS

- 7.1 Races should not be started when the Race Committee deems that winds are consistently at or above 23 knots or gusting to 25 knots and above. If a race has been started and the wind increases to 25 knots and above, it remains at the discretion of the Race Committee whether or not to abandon the race. Races should not be started unless winds are consistently above five (5) knots at the time of the start.